

Engineering Specification

Job Name _____	Contractor _____
Job Location _____	Approval _____
Engineer _____	Contractor's P.O. No. _____
Approval _____	Representative _____

Model LDS-3 Point Electronic Water Flow Monitor and Alarm System



Overview

The LDS-3 is an electronic water flow monitor and alarm system designed to detect leaks in water pipes, plumbing fixtures and water-using appliances. Monitor water flow 24/7 and set your time/flow parameters from the included wireless control panel or your mobile device with our free app.

How it Works

If continuous water flow exceeds your pre set limits, an alarm is triggered. If this occurs, you will receive a notification on your mobile device, an audible alarm will sound on the control panel and the water supply will be shut off, potentially preventing major water damage.

Available Sizes	3/4"	1"	1.25"	1.5"	2"	2.5"	3.0"
------------------------	------	----	-------	------	----	------	------

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

Model Number	Pipe Size	Dimensions (H x W x L)	Weight
LDS-3-075	3/4"	10" x 9" x 8"	6 lbs
LDS-3-100	1.0"	10" x 9" x 8"	7 lbs
LDS-3-125	1.25"	10" x 9" x 8"	8 lbs
LDS-3-150	1.5"	10" x 10" x 8"	9 lbs
LDS-3-200	2.0"	13" x 11" x 9"	12 lbs
LDS-3-250	2.5"	15" x 12" x 10"	18 lbs
LDS-3-300	3.0"	16" x 13" x 10"	24 lbs

Features

- FREE Smart phone app allows you to remotely see the system status and to open or close the valve from anywhere in the world
- Water movement/leak sensitivity down to .001 GPM on ¾" systems 24hrs by 365days without ever needing to shut off water
- Control panel allows the user to easily open or close the water valve to stop water flow at any time
- Includes three different adjustable settings for protection while home, away, or on standby
- Valve Open/Close Cycle Time – 8 seconds to 30 seconds (size dependent)
- Manual Over-ride Valve Open/Close Handle; no special tools required
- Valve to Control-Panel Interface – wireless 433MHz, or Wired RS-485
- Actuator Torque Values 133 in-lbs. to 1960 in-lbs. (size dependent)
- Compatible with all domestic cold and hot water pipe systems
- Installation Orientation – No restrictions; vertical/horizontal 360°
- Transformer Power Supplies Included for all devices
- Overload Torque Protection Electronics
- Max Water Pressure 600 PSI at 176F
- Max Water Pressure 400 PSI at 250F
- Actuator Anti-Condensation Heater
- UL1951, CSA C22.2 No. 14, 18



A WATTS Brand

USA: T: (760) 884-8300 • Sales@senthdro.com • LeakDefenseSystem.com