

Engineering Specification

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Model POLS-W

Wired Point of Leak Sensor



Overview

The Wired Point of Leak Sensor (POLS) provides a way to sense moisture on any non-conductive surface. It is wired directly to the Leak Defense System® Control Panel and, when moisture is detected, will send a signal to initiate an alarm condition. The POLS should be placed such that the two probes firmly touch the surface to be protected. The POLS is completely self-contained and preset at the factory.

Features

- Dimensions: 1 5/16" diameter x 1 1/4" high
- Cord length: Approximately 5'
- Durable water-resistant plastic enclosure designed to be installed in a typically dry location
- Includes sensor, self-adhesive wire tie and holder, and instructions

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

LEAK DEFENSE®

A **WATTS Brand**

USA: T: (760) 884-8300 • Sales@senthidro.com • LeakDefenseSystem.com